
Table of Contents

CHAPTER 1: Introduction 1-1

- 1.1 General Information 1-1
- 1.1 Backward compatibility 1-2
- 1.2 Organization of This Manual 1-2

CHAPTER 2: Physics-Based Derivation of I-V Model 2-1

- 2.1 Non-Uniform Doping and Small Channel Effects on Threshold Voltage 2-1
 - 2.1.1 Vertical Non-Uniform Doping Effect 2-3
 - 2.1.2 Lateral Non-Uniform Doping Effect 2-5
 - 2.1.3 Short Channel Effect 2-7
 - 2.1.4 Narrow Channel Effect 2-12
- 2.2 Mobility Model 2-15
- 2.3 Carrier Drift Velocity 2-17
- 2.4 Bulk Charge Effect 2-18
- 2.5 Strong Inversion Drain Current (Linear Regime) 2-19
 - 2.5.1 Intrinsic Case ($R_{ds}=0$) 2-19
 - 2.5.2 Extrinsic Case ($R_{ds}>0$) 2-21
- 2.6 Strong Inversion Current and Output Resistance (Saturation Regime) 2-22
 - 2.6.1 Channel Length Modulation (CLM) 2-25
 - 2.6.2 Drain-Induced Barrier Lowering (DIBL) 2-26
 - 2.6.3 Current Expression without Substrate Current Induced Body Effect 2-27
 - 2.6.4 Current Expression with Substrate Current Induced Body Effect 2-28
- 2.7 Subthreshold Drain Current 2-30
- 2.8 Effective Channel Length and Width 2-31
- 2.9 Poly Gate Depletion Effect 2-33

CHAPTER 3: Unified I-V Model 3-1

- 3.1 Unified Channel Charge Density Expression 3-1
- 3.2 Unified Mobility Expression 3-6

3.3 Unified Linear Current Expression	3-7
3.3.1	Intrinsic case ($R_{ds}=0$) 3-7
3.3.2	Extrinsic Case ($R_{ds} > 0$) 3-9
3.4 Unified V_{dsat} Expression	3-9
3.4.1	Intrinsic case ($R_{ds}=0$) 3-9
3.4.2	Extrinsic Case ($R_{ds}>0$) 3-10
3.5 Unified Saturation Current Expression	3-11
3.6 Single Current Expression for All Operating Regimes of V_{gs} and V_{ds}	3-12
3.7 Substrate Current	3-15
3.8 A Note on V_{bs}	3-15

CHAPTER 4: Capacitance Modeling 4-1

4.1 General Description of Capacitance Modeling	4-1
4.2 Geometry Definition for C-V Modeling	4-2
4.3 Methodology for Intrinsic Capacitance Modeling	4-4
4.3.1	Basic Formulation 4-4
4.3.2	Short Channel Model 4-7
4.3.3	Single Equation Formulation 4-9
4.4 Charge-Thickness Capacitance Model	4-14
4.5 Extrinsic Capacitance	4-19
4.5.1	Fringing Capacitance 4-19
4.5.2	Overlap Capacitance 4-19

CHAPTER 5: Non-Quasi Static Model 5-1

5.1 Background Information	5-1
5.2 The NQS Model	5-1
5.3 Model Formulation	5-2
5.3.1	SPICE sub-circuit for NQS model 5-3
5.3.2	Relaxation time 5-4
5.3.3	Terminal charging current and charge partitioning 5-5
5.3.4	Derivation of nodal conductances 5-7

CHAPTER 6:	Parameter Extraction	6-1
6.1	Optimization strategy	6-1
6.2	Extraction Strategies	6-2
6.3	Extraction Procedure	6-2
6.3.1	Parameter Extraction Requirements	6-2
6.3.2	Optimization	6-4
6.3.3	Extraction Routine	6-6
6.4	Notes on Parameter Extraction	6-14
6.4.1	Parameters with Special Notes	6-14
6.4.2	Explanation of Notes	6-15
CHAPTER 7:	Benchmark Test Results	7-1
7.1	Benchmark Test Types	7-1
7.2	Benchmark Test Results	7-2
CHAPTER 8:	Noise Modeling	8-1
8.1	Flicker Noise	8-1
8.1.1	Parameters	8-1
8.1.2	Formulations	8-2
8.2	Channel Thermal Noise	8-4
8.3	Noise Model Flag	8-5
CHAPTER 9:	MOS Diode Modeling	9-1
9.1	Diode IV Model	9-1
9.1.1	Modeling the S/B Diode	9-1
9.1.2	Modeling the D/B Diode	9-3
9.2	MOS Diode Capacitance Model	9-5
9.2.1	S/B Junction Capacitance	9-5
9.2.2	D/B Junction Capacitance	9-7
9.2.3	Temperature Dependence of Junction Capacitance	9-10

APPENDIX A: Parameter List A-1

A.1 Model Control Parameters A-1

A.2 DC Parameters A-1

A.3 C-V Model Parameters A-6

A.4 NQS Parameters A-8

A.5 dW and dL Parameters A-9

A.6 Temperature Parameters A-10

A.7 Flicker Noise Model Parameters A-12

A.8 Process Parameters A-13

A.9 Geometry Range Parameters A-14

A.10 Model Parameter Notes A-14

APPENDIX B: Equation List B-1

B.1 I-V Model B-1

B.1.1 Threshold Voltage B-1

B.1.2 Effective ($V_{gs}-V_{th}$) B-2

B.1.3 Mobility B-3

B.1.4 Drain Saturation Voltage B-4

B.1.5 Effective V_{ds} B-5

B.1.6 Drain Current Expression B-5

B.1.7 Substrate Current B-6

B.1.8 Polysilicon Depletion Effect B-7

B.1.9 Effective Channel Length and Width B-7

B.1.10 Source/Drain Resistance B-8

B.1.11 Temperature Effects B-8

B.2 Capacitance Model Equations B-9

B.2.1 Dimension Dependence B-9

B.2.2 Overlap Capacitance B-10

B.2.3 Intrinsic Charges B-12

APPENDIX C: References C-1

APPENDIX D: Model Parameter Binning D-1

D.1 Model Control Parameters D-2

D.2 DC Parameters D-2

D.3 AC and Capacitance Parameters D-7

D.4 NQS Parameters D-9

D.5 dW and dL Parameters D-9

D.6 Temperature Parameters D-11

D.7 Flicker Noise Model Parameters D-12

D.8 Process Parameters D-13

D.9 Geometry Range Parameters D-14

